IN THE CLAIMS:

Please amend claim 11 to read as follows:

1. (original) A solid oxide fuel system component which is adapted to be exposed to an oxidising atmosphere in the fuel system system and which is formed of a heat resistant allow having a composition, in wt%, of:

AI 5.0-10.0

Si 0.1-3.8

 $Mn \leq 0.5$

 $Cu \leq 0.23$

 $Ni \leq 0.61$

 $C \leq 0.02$

 $P \leq 0.04$

 $S \leq 0.04$

Cr < 5.0,

and residue Fe, excluding incidental impurities.

- 2. (original) A solid oxide fuel system component according to claim 1, which contains no more than about 8.5 wt% Al.
- 3. (previously amended) A solid oxide fuel cell system component according to claim 1 which contains less than 0.05 wt% Mn.
- 4. (previously amended) A solid oxide fuel cell system component according to claim 1 wherein the alloy has a composition, in wt%, of:

AI 6.0 ± 1.0

Si 1.0 ± 0.5

C 0.005 - 0.02

P ≤ 0.04

S ≤ 0.04

Cr ≤ 0.10

(AI + Si) = 6.5 to 7.5

Residue Fe, excluding incidental impurities.

5. (previously amended) A solid oxide fuel cell system component according to claim 1 wherein the alloy contains no Cr.

- 6. (previously amended) A solid oxide fuel cell system component according to claim 1 having a surface layer of Al₂O₃.
- 7. (original) A solid oxide fuel system component according to claim 6 wherein the Al₂O₃ surface layer has a thickness in the range of from about 1 to about 10 microns, preferably from about 1 to about 3 microns.
- 8. (previously amended) A solid oxide fuel cell system component according to claim 1 wherein source material for the alloy at least includes scrap metal.
- 9. (amended) A solid oxide fuel cell system component according to claim 1 which is a gas separator disposed or adapted to be disposed between adjacent fuel cells in the system.
- 10. (amended) A solid oxide fuel cell system component according to claim 1 which is a component selected from the group consisting of a manifold, a base plate, a current collector strap, ducting, a heat exchanger and a heat exchanger plate disposed or adapted to be disposed in the solid oxide fuel cell system.
- 11. (currently amended) A solid oxide fuel cell system in which one or more components adapted to be exposed to a temperature in excess of 750°C and an oxidising atmosphere are in accordance with any one of the preceding claims claim 1.